

In re Patent Application of  
**PAU ET AL.**  
Serial No. **Not Yet Assigned**  
Filed: **Herewith**

---

5. A method of calculating the discrete cosine transform (DCT) of blocks of pixels of an image, comprising the steps of:

defining first subdivision blocks as range blocks, having a fractional and scalable size  $N/2^i * N/2^i$ , where  $i$  is an integer;

defining second subdivision blocks of  $N*N$  pixels as domain blocks, shiftable by intervals of  $N/2^i$  pixels; and

calculating, in parallel, the DCT of  $2^i$  range blocks of a domain block of  $N*N$  pixels of the image.

6. A method according to Claim 5, wherein the step of calculating comprises the steps of:

a) ordering the pixels in the range blocks of a certain dimension by rearranging input pixels in  $2^i$  vectors of  $2^i$  components;

b) calculating, in parallel,  $2^i$  monodimensional DCTs by processing the vectors defined in the step a);

c) arranging output sequences of the monodimensional DCTs relative to the  $2^i$  vectors;

d) completing the calculation in parallel of  $2^i$  bidimensional DCTs by processing output sequences of monodimensional DCTs produced in step c); and

e) arranging output sequences of bidimensional DCTs generated in step d) in  $2^i$  vectors of bidimensional DCT coefficients.

7. A method according to Claim 6, wherein the step of calculating  $2^i$  monodimensional DCTs in parallel in step b)

In re Patent Application of  
**PAU ET AL.**  
Serial No. **Not Yet Assigned**  
Filed: **Herewith**

---

and the step of completing the parallel calculation of  $2^i$  bidimensional DCTs of step d) are performed by subdividing the sequences resulting from step a) and from step c), respectively, in groups of scalar elements, calculating the sums and differences thereof by way of adders and subtractors and by reiterately multiplying the sum and difference results by respective coefficients until completing the calculation of the relative DCT coefficients, respectively monodimensional and bidimensional.

8. A method of compressing data of an image to be stored or transmitted, comprising the steps of:

defining first subdivision blocks as range blocks, having a fractional and scalable size  $N/2^i * N/2^i$ , where  $i$  is an integer;

defining second subdivision blocks of  $N*N$  pixels as domain blocks, shiftable by intervals of  $N/2^i$  pixels;

calculating, in parallel, the DCT of  $2^i$  range blocks and of a relative domain block;

classifying the transformed range blocks according to their relative complexity represented by a sum of values of three AC coefficients;

applying a fractal transform in the DCT domain to data of the range blocks whose complexity classification exceeds a pre-defined threshold and only storing a DC coefficient of the range blocks with a complexity lower than the threshold, while identifying a relative domain block to which the range block in a transformation belongs that produces a best fractal approximation of the range block;

In re Patent Application of  
**PAU ET AL.**  
Serial No. **Not Yet Assigned**  
Filed: **Herewith**

---

calculating a difference between each range block and its fractal approximation;

quantizing the difference in the DCT domain by using a quantization table preestablished in consideration of human sight characteristics;

coding the quantized difference by a process based on probabilities of quantization coefficients; and

storing or transmitting code of each range block compressed in the DCT domain and the DC coefficient of each uncompressed range block.

9. An apparatus for calculating the discrete cosine transform (DCT) of blocks of pixels of an image, the apparatus comprising:

means for defining first subdivision blocks as range blocks, having a fractional and scalable size  $N/2^i * N/2^i$ , where  $i$  is an integer;

means for defining second subdivision blocks of  $N*N$  pixels as domain blocks, shiftable by intervals of  $N/2^i$  pixels; and

means for calculating, in parallel, the DCT of  $2^i$  range blocks of a domain block of  $N*N$  pixels of the image.

10. An apparatus according to Claim 9, wherein the means for calculating comprises:

means for ordering the pixels in the range blocks of a certain dimension by rearranging input pixels in  $2^i$  vectors of  $2^i$  components;

In re Patent Application of  
**PAU ET AL.**  
Serial No. **Not Yet Assigned**  
Filed: **Herewith**

---

means for calculating, in parallel,  $2^i$   
monodimensional DCTs by processing the vectors defined by the  
means for calculating;

means for arranging output sequences of the  
monodimensional DCTs relative to the  $2^i$  vectors;

means for completing the calculation in parallel of  
 $2^i$  bidimensional DCTs by processing output sequences of  
monodimensional DCTs produced by the means for arranging output  
sequences of the monodimensional DCTs; and

means for arranging output sequences of  
bidimensional DCTs, generated by the means for completing the  
calculation, in  $2^i$  vectors of bidimensional DCT coefficients.

11. An apparatus according to Claim 10, wherein the  
means for calculating  $2^i$  monodimensional DCTs in parallel in  
and the means for completing the parallel calculation of  $2^i$   
bidimensional DCTs are for subdividing the sequences resulting  
from the means for ordering and the means for arranging output  
sequences of the monodimensional DCTs, respectively, in groups  
of scalar elements, calculating the sums and differences  
thereof by way of adders and subtractors and by reiterately  
multiplying the sum and difference results by respective  
coefficients until completing the calculation of the relative  
DCT coefficients, respectively monodimensional and  
bidimensional.

12. An apparatus for compressing data of an image  
to be stored or transmitted, comprising:

In re Patent Application of  
**PAU ET AL.**  
Serial No. **Not Yet Assigned**  
Filed: **Herewith**

---

means for defining first subdivision blocks as range blocks, having a fractional and scalable size  $N/2^i * N/2^i$ , where  $i$  is an integer;

means for defining second subdivision blocks of  $N*N$  pixels as domain blocks, shiftable by intervals of  $N/2^i$  pixels;

means for calculating, in parallel, the DCT of  $2^i$  range blocks and of a relative domain block;

means for classifying the transformed range blocks according to their relative complexity represented by a sum of values of three AC coefficients;

means for applying a fractal transform in the DCT domain to data of the range blocks whose complexity classification exceeds a pre-defined threshold and only storing a DC coefficient of the range blocks with a complexity lower than the threshold, while identifying a relative domain block to which the range block in a transformation belongs that produces a best fractal approximation of the range block;

means for calculating a difference between each range block and its fractal approximation;

means for quantizing the difference in the DCT domain by using a quantization table preestablished in consideration of human sight characteristics;

means for coding the quantized difference by a process based on probabilities of quantization coefficients; and

means for storing or transmitting code of each range block compressed in the DCT domain and the DC coefficient of each uncompressed range block.